

Pull Test Ring

Product code: PRING

Product specification: For Friction bolts

Category: Rock Bolts – Bolt Fittings

Introduction

Designed to be used with Sandvik pull test equipment. The pull ring is fitted to friction bolts prior to installation. The ring allows measured load to be safely applied to installed friction bolts for the purpose of pull testing.

Key features

- Full test rings are available for 47mm, 39mm and 33mm friction bolts
- Can be supplied in black or hot dipped galvanised.
- Forged steel rings are made from Grade AS1442-1045
- Cast carbon steel rings are made from Grade: AS2074/C5 grade.
- Double Flanged Pull test rings available.
- Machined steel pull test rings available on request.



Product Code Guide

Forged Steel (Galvanized)

Cast Carbon Steel (Galvanized)

PRING47FOG

PRING47CG

Physical properties

	Effective use	Length	Flange diameter	Mass
PRING47FOG	16t	40.0mm	70.0mm	380g
PRING47CG	16t	40.0mm	70.0mm	380g

Notes


Only Sandvik rock bolt components should be used to enable the optimum performance of the bolt system to be obtained

Ground Support is Quality Assured to ISO 9001:2015

Product range and accessories

- Sandvik manufactures a comprehensive range of plates specifically designed for this range of Bolts

Typically used plates

Product group	Dragon Fly	Friction Bolts	Plates	Pull Ring
Product imagery				
Product code prefix	DF	FB	TDD	PRING

Phone app

Want to know more; our full product range, knowledge centre, and other details are available via the App; available on iOS and Android devices by searching “Ground Support”.



Legal disclaimer

All dimensions, weights, quantities, and specifications are those applicable at the time of this publication and may be amended from time to time. Please contact your local representative for final confirmation of any key specifications.